HydroSense Application Data Sheet (2 pages)

Please fill in as much information as possible. Some information is required to determine the suitability of the instrument. Other information will help us understand your application better. We may be able to provide some further installation and monitoring guidance.

1.	Agent/Representative FLOWMASTER, INC.				
2.	Prepared by 11529 INVESTOR AVE.				
2	BATON ROUGE, LA 70807-4261 3. End User Information				
Э.	End Oser Information				
Na	me:				
Ad	dress:				
0	0-1-1				
Sit	e: Contact Tel:				
	101				
4.	 Application Description (brief overview of process and reason for monitoring the water for hydrocarbons) 				
P.B. serve Q					
	1 (okuratu) (
_					
5.	Water Source Description 19569 INVIDE				
sump pitprocess tankprocess pipevesselditchopen channelseparatorwelloffshore platformcooling water pipeother					
6.	Water Type				
storm waterwaste watertreated waterprocess watercooling watercondensatedrinking watersewerground watersea waterdistilled waterproduced waterother					
7.	Compound to be monitored (describe the contaminant, chemical name, structure, source etc.)				
mir	nimum ppm to be measured, maximum ppm to be measured				
8.	Are there other contaminants or products in the water ? Describe				
	Do they vary in their concentrations ?				
9.	Is there any colour in the water?Describe Are there any suspended solids (turbidity) in the water ?				
10.					
	What range? Describe				
	DESCRIBE				

Process Information

11.	Is there a continuous sample flow available to the HydroSense?				
13	What is the flow range ?				
	What is the pressure in the stream line to the HydroSense?				
15.	Can the sample stream outfall from the HydroSense go to an open drain or containment?				
16.	. Is the sample stream pumped from the process source to the HydroSense?				
	If yes, what type of pump?				
17.	What is the process sample stream temperature range				
18.	What is the room or outdoor HydroSense enclosure location temperature range				
19.	Area Classification of HydroSense installation:	General Purpose	Type 12		
			Type 4		
		Hazardous	Zone 0		
			Zone 1		
20	What is the input power available?24 vdc110 vac	220 yac	Zone 2		
21.	I. Are the relays being used? Describe				
	Is the 4-20 mA output being used? Describe				
	21. Do you presently have grab samples tested?laboratory on sitesend to outside lab. What				
	technique and compounds are measured?				
23.	Does the process ppm concentration vary on a regular basis ?				
	4. Do you have the ability to force a change or make up a ppm in water sample for calibration purpo				
	?				
	Is the monitoring intent to determine an upset condition or to record and evaluate actual ppm levels? Describe				
26.	The HydroSense uses a UV Fluorescence technique to mor	nitor oil in water. The wa	avelengths used		
	are selective to aromatic hydrocarbons in the water. Aromatics are generally proportional to total				
	petroleum hydrocarbons and are used as an indicator of ppm concentrations in water. The instrument				
	UV fluorescence response is used to correlate to the user inputted calibration values. Changes in				
	the make-up of the oils may affect the accuracy and a site calibration is therefore required. This technique has been review with the end user. Yes No				
27.	A regular cleaning involves a wipe down of the glass tile and visual inspection of the flow and weir.				
	This is a 2 minute procedure. The frequency should be daily for one week, then every other day,				
	and then progressively less frequent until an adequate frequency is determined to keep the unit				
	pperational. This maintenance has been reviewed with the end user Yes No				